

GENERAL INFO

TABLE OF INTER-CHANGEABILITY

Rim	Standard size	85 series	80 series	75 series	70 series	65 series	60 series	55-50 series	Radial narrow (metric)	Radial narrow (imperial)
16	6.50R16				260/70R16	280/65R16				
	7.50R16		250/80R16		280/70R16	320/65R16				
18	7.50R18		250/80R18		280/70R18	320/65R18				
20	7.50R20				280/70R20	340/65R18				
	9.5R20	250//85R20	260/80R20		300/70R20	340/65R20				
	11.2R20	280/85R20			320/70R20					
20	12.4R20	320/85R20	340/80R20		360/70R20	420/65R20				
		250/85R24			300/70R24					
24	8.3R24	280/85R20			320/70R20					
	9.5R24	320/85R20	340/80R20		360/70R20	420/65R20				
		250/85R24			300/70R24					
	11.2R24	280/85R24			320/70R24	440/65R20				
	12.4R24	320/85R24			360/70R24	420/65R24				
	13.6R24	340/85R24			380/70R24	440/65R24		210/95R32	8.3R32	
14.9R24	380/85R24			420/70R24	480/65R24			230/95R32	9.5R32	
16.9R24	420/85R24			480/70R24	540/65R24			270/95R32	11.2R32	
26	14.9R26				380/70R28	540/65R24				
	16.9R26				480/70R26	540/65R26			230/95R36	9.5R36
									320/90R32	
	18.4R26				480/70R28	540/65R28	600/60R28	750/50R26	270/95R36	11.2R36
									230/95R38	9.5R38
	23.1R26			620/75R26	600/70R30	600/65R32	710/60R30	1000/50R25		
26	28LR26			620/75R26	600/70R30	600/65R32	710/60R30	1000/50R25		
					650/70R26	750/65R26		750/55R30		
					650/70R26	750/65R26		750/55R30		
28	9.5R28	250/85R28			360/70R24	340/65R28				
	11.2R28	280/85R28			320/70R28	440/65R24		210/95R32	8.3R32	
	12.4R28	320/85R28			360/70R28	420/65R28				
	13.6R28	340/85R28			380/70R28	440/65R28	480/60R28		270/95R32	11.2R32
	14.9R28	380/85R28			420/70R28	480/65R28	520/60R28		230/95R36	9.5R36
	16.9R28	420/85R28			480/70R28	540/65R28	600/60R28	750/50R26	320/90R32	11.2R36
30	14.9R30	380/85R30			480/70R28	540/65R28			320/90R32	11.2R36
					420/70R30			270/95R36		
	16.9R30	420/85R30			480/70R30	540/65R30	600/60R30	750/55R26	270/95R38	11.2R38
					600/65R28				230/95R40	
	18.4R30	460/85R30			520/70R30	600/65R30		710/55R30	420/90R30	8.3R44
30		320/85R38			600/70R28	600/65R30			210/95R44	
	23.1R30			620/75R30	480/70R38	540/65R38	600/60R38		300/95R42	

Rim	Standard size	85 series	80 series	75 series	70 series	65 series	60 series	55-50 series	Radial narrow (metric)	Radial narrow (imperial)
32	12.4R32	320/85R32								230/95R38
	24.5R32			650/75R32	680/70R32		800/60R32			
	30.5LR32			620/75R34						
32				680/75R32		800/65R32	710/60R38	900/55R32		
				650/75R34	680/70R34	750/65R34		1050/50R32	340/85R48	
34	14.9R34	380/85R34								
	16.9R34	420/85R34		400/75R38	480/70R34	540/65R34	710/60R30	750/55R30	230/95R44	9.5R44
	18.4R34	460/85R34			520/70R34	600/65R34			270/95R44	11.2R44
	23.1R34			620/75R34	520/70R38	600/65R38				
36				650/75R32		650/65R34				
	11.2R36	320/85R34							320/90R32	
	12.4R36	320/85R36			480/70R30	540/65R30	600/60R30	750/55R26	270/95R38	11.2R38
36	13.6R36	340/85R36			520/70R30					
		380/85R34			600/70R28	600/65R30		710/55R30	210/95R44	8.3R44
		460/85R30								
38	12.4R38	320/85R38								
	13.6R38	340/85R38	380/80R38	400/75R38		540/65R34	710/60R30	750/55R30	230/95R44	9.5R44
	14.9R38	380/85R38			520/70R34	600/65R34				
		460/85R34			520/70R34					
	16.9R38	420/85R38		620/75R30	480/70R38	540/65R38	600/60R38		300/95R42	
					600/70R34				230/95R48	9.5R48
38	18.4R38	460/85R38		620/75R34	520/70R38	600/65R38	650/60R38		300/95R46	12.4R46
				650/75R32	680/70R32	650/65R34	710/60R34		270/95R48	11.2R48
	20.8R38	520/85R38	480/80R42	420/80R46	680/75R32	580/70R38	650/65R38	900/55R32	380/90R46	
42								1050/50R32	340/85R48	
	18.4R42	460/85R42	480/80R42	680/75R32	580/70R38	600/65R42		900/55R32	340/85R48	
		340/85R48	420/80R46		620/70R38	650/65R38		1050/50R32	320/90R50	
	20.8R42	520/85R42		650/75R38	580/70R42	650/65R42	710/60R42		300/95R52	12.4R52
		680/85R32		710/75R34	620/70R42		900/60R32	900/50R42	270/95R54	11.2R54
			480/80R46		710/70R38				320/90R54	
46					800/70R32					
	20.8R46	520/85R46		650/75R42	800/70R38					
46		650/85R38	480/80R50	800/75R32	710/70R42	650/65R46	900/60R38		380/90R50	
					620/70R46					
HV		710/85R38		710/75R42			900/60R42			

This table of inter-changeability for equivalent sizes is based upon ETRTO Speed Radius Index (SRI) and is for guidance only. For any change of tyre size it is important to calculate & check the lead/lag percentage and to ensure sufficient height/width clearance of tyre/vehicle combination. Sizes in bold text are available from the Firestone Europe range of Agricultural tyres. This table does not include Agro Industrial nor Firestone America Products.